



TUMBLE DRYER

Model No.

LPD-700-34, LPD-1000-50

LE PROTEK TUMBLE DRYER

We are committed to designing the most efficient tumble dryers, recognizing their crucial role in your laundry operations. Standard axial airflow. With features such as inverter motors, belt driving, drum insulation and more, our machines are engineered to enhance energy efficiency while operating smoothly and quietly.

ADVANTAGE AND FEATURE

- Stainless steel cylinder anti-corrosion.
- Clad steel front and side panels resist rust and fingerprints, ensuring a pristine appearance for your laundry.
- Large door with 180° opening for easy loading and unloading.
- Heavy-duty door hinge ensures prolonged machine operation.
- Inverter drive motor for soft start/stop, reduced noise, and extended belt life.
- Inverter fan motor allows for adjustable airflow speeds.
- Standard reversing cylinder prevents linen tangling.
- Standard axial airflow.
- Large lint filter.
- Stacked tumble dryer design saves space.



PRODUCT PARAMETER:

MODEL		LPD-700-34	LPD-1000-50
Control		Touch	Touch
Capacity	kg	34	50
Reversing Drum	/	Yes	Yes
Cylinder Diameter	mm	903	1130
Cylinder Depth	mm	1024	952
Volume	liter	656	954
Gas Inlet	inch	1/2	3/4
Steam Inlet	inch	1/2	1
Steam Outlet	inch	3/4	3/4
Compressed air inlet*	mm	8	8
Exhaust	mm	200	245
Motor Power / Drive Motor	kW	0.75	1.5
Fan Power	kW	0.55	2.2
Electric Heating	RPM	36	45
Power Supply	-	220V/50Hz/60Hz/1ph 380V/50Hz/60Hz/3ph	380V/50Hz/3Ph
Door Centre to Floor	mm	1052	1147
Overall Width	mm	978	1320
Overall Depth	mm	1318	1775
Overall Height	mm	1816	1946
Net Weight	kg	270	800
Packing Width	mm	1078	1420
Packing Depth	mm	1418	1875
Packing Height	mm	1966	2096