



TUMBLE DRYER

Model No.

LPD-2000-100

LE PROTEK TUMBLE DRYER

We are committed to designing the most efficient tumble dryers, recognizing their crucial role in your laundry operations. Standard axial airflow. With features such as inverter motors, belt driving, drum insulation and more, our machines are engineered to enhance energy efficiency while operating smoothly and quietly.

FEATURE

- Reversing Stainless steel cylinder.
- Painted carbon steel panels.
- Super large door with 180° opening. Optional slid door or flip door.
- Heavy-duty door hinge ensures prolonged machine operation.
- Inverter drive motor and fan motor.
- 3D airflow and heat isolation.
- Optional moisture sensor.
- Optional forward tilting for 100kg slide door or flip door models.

PRODUCT PARAMETER:

| MODEL | LPD-2000-100 | |
|-----------------------|--------------|---------------------------------|
| Control | | Touch |
| Capacity | kg | 100 |
| Reversing Drum | / | Yes |
| Cylinder Diameter | mm | 1462 |
| Cylinder Depth | mm | 1170 |
| Volume | liter | 1964 |
| Gas Heating Inlet | inch | ¾ |
| Steam Heating Inlet | inch | 1 |
| Steam Outlet | inch | 3/4 |
| Compressed air inlet* | mm | 8 |
| Exhaust | mm | 295 |
| Drive Motor | kW | 2.2 |
| Fan Power | kW | 3 |
| Electric Heating | RPM | 72 |
| Power Supply | - | 380V/50Hz/3ph |
| Door Centre to Floor | mm | 1442 |
| Overall Width | mm | 1647 |
| Overall Depth | mm | 1880 |
| Overall Height | mm | 2436 |
| Net Weight | kg | 1220 |
| Packing Width | mm | Body 1747/ heating element 1400 |
| Packing Depth | mm | Body 1980/ heating element 1500 |
| Packing Height | mm | Body 1700/ heating element 800 |