t

DRY CLEANING MACHINE

Model No.

LPDM-P18E

LE PROTEK DRY CLEANING MACHINE

QUALITY EXPERT

All components contacting solvents are 304 stainless steels. All electrical components are high-end brands and CE certified.

PERFORMANCE EXPERT

- The high-performance LCD control panel supports man-machine dialogue, provides programmability, and allows for easy switching between automatic mode and manual mode.
- Programmable detergent pump, through computer or manual control, to ensure accurate solvent injection.

FEATURE

- Reversing Stainless steel cylinder.
- All stainless-steel structure
- Solvent leak-proof base complies with CE standard
- Refrigeration and heat pump recycling system

- Centrifugal filter with high precision filer sheets that no need for filter powder or carbon powder.
- Cartridge filter for removing colors, odor and particles.
- Inverter drive motor and fan motor.
- Multi safety guards.
- Auto detergent injection.
- Second water separator.
- Standard auto-dry that adjusts drying time depending on load (except for the 8kg).
- Optional solvent cooling.
- Optional distiller self-cleaning.
- External carbon-based absorption system.

PRODUCT PARAMETER

MODEL		LPDM-P18E
Capacity	kg	18
Cylinder	mm	903
Cylinder Depth	mm	524
Volume	liter	342
Wash Speed	r.p.m	42
Extract Speed	r.p.m	650
Solvent tank 1	liter	145
Solvent tank 2	liter	145
Solvent tank 3	liter	206
Distillation	liter	220
ELECTRIC POWER		
Washing Motor	kW	3.5
Solvent Pump Motor	kW	1.1
Fan Motor	kW	2.2
Compressor	kW	4.5
Filter Motor	kW	0.12
Carbon Absorber Fan	kW	1.1
Distillation Heating Power*	kW	11.1
Drying Heating Power*	kW	6.9
Carbon Removal Heating Power	kW	6.6
CONNECTION		
Power Supply	380V/50Hz/3Ph	
Inlet	“	1”
Drain	“	1”
Steam inlet	“	½”
Steam outlet	“	½”

Compressed air	mm	Ø8
DIMENSIONS		
Depth	mm	2140
Width	mm	1550
Height	mm	2290
Net Weight	Kg	1800
Packing Depth	mm	2240
Packing Width	mm	1650
Packing Height	mm	2440