



<sup>t</sup>  
**MULTI-SOLVENT  
DRY CLEANING MACHINE**

**Model No.**  
LPMSDM-H18E

# LE PROTEK

## MULTI-SOLVENT DRY CLEANING MACHINE

### PERFORMANCE EXPERT

- Unique dual-invertor driving system ensures significant energy savings, smoother machine peration and minimal noise.
- Patent - designed solvent tank with bottom self - cleaning functionality.

### ENERGY SAVING EXPERT

- The meticulously designed drying chamber significantly improves the flow of air and solvent vapor into the recovery chamber, reducing recycling time, increasing productivity, and achieving substantial energy savings.
- Two sets of temperature - controlled water valves adjust water flow automatically according to the refrigeration temperature.
- Optional water - cooling or air - cooling systems.



## **FEATURE**

- Compatible with various solvents including hydrocarbon, silicone-based solvents, K4 and modified alcohols.
- Solvent recycles through segment vacuum distilling.
- Advanced anti-statistic technology.
- System prevents over distilling.
- Auto nitrogen injection system.
- Multi-level pressure and temperature safety guard.

## **PRODUCT PARAMETER**

MODEL	LPMSDM-H18E	
Capacity	kg	18
Cylinder Diameter	mm	903
Cylinder Depth	mm	534
Volume	liter	342
Wash Speed	r.p.m	42
Extract Speed	r.p.m	650
Solvent tank 1	liter	145
Solvent tank 2	liter	145
Solvent tank 3	liter	206
Distillation Tank	liter	206
<b>ELECTRIC POWER</b>		
Washing Motor	kW	3.5
Solvent Pump Motor	kW	1.1
Fan Motor	kW	1.5
Compressor Motor	kW	4.5
Filter Motor	kW	0.12
Vacuum Pump	kW	1.5
Distillation Heating Power	kW	11
Drying Heating	kW	11
<b>CONNECTION</b>		
Power Supply	380V/50Hz/3Ph	
Inlet	“	1”
Drain	“	1”
Steam inlet	“	½”
Steam outlet	“	½”
Compressed air	mm	Ø8

DIMENSIONS		
Depth	mm	2140
Width	mm	1550
Height	mm	2290
<b>Net Weight</b>	<b>Kg</b>	<b>1900</b>
Packing Depth	mm	2240
Packing Width	mm	1650
Packing Height	mm	2440

