



^t
**MULTI-SOLVENT
DRY CLEANING MACHINE**

**Model No.
LPMSDM-H28E**

LE PROTEK

MULTI-SOLVENT DRY CLEANING MACHINE

OPTIONS

- World's first softmount dry cleaning machine features high-speed spin of up to 900RPM.
- Contact us for other requests

ENERGY SAVING EXPERT

- The meticulously designed drying chamber significantly improves the flow of air and solvent vapor into the recovery chamber, reducing recycling time, increasing productivity, and achieving substantial energy savings.
- Two sets of temperature - controlled water valves adjust water flow automatically according to the refrigeration temperature.
- Optional water - cooling or air - cooling systems.



FEATURE

- Compatible with various solvents including hydrocarbon, silicone-based solvents, K4 and modified alcohols.
- Solvent recycles through segment vacuum distilling.
- Advanced anti-statistic technology.
- System prevents over distilling.
- Auto nitrogen injection system.
- Multi-level pressure and temperature safety guard.

PRODUCT PARAMETER



MODEL		LPMSDM-H28E
Solvent		Multi Solvent hydrocarbon/Silicone based solvents/K4/modified alcohols.
Capacity	kg	28
Cylinder Diameter	mm	990
Cylinder Depth	mm	685
Volume	liter	528
Wash Speed	r.p.m	35
Extract Speed	r.p.m	900
Solvent tank 1	liter	236
Solvent tank 2	liter	236
Solvent tank 3	liter	287
Distillation Tank	liter	396
ELECTRIC POWER		
Washing Motor	kW	11
Solvent Pump Motor	kW	1.1
Fan Motor	kW	2.2
Compressor Motor	kW	6.6
Filter Motor	kW	0.12
Carbon Absorber Fan	kW	NA
Vacuum Pump	kW	1.5
CONNECTION FOR STEAM HEATING		
Power Supply	380V/50Hz/3Ph	
Inlet	“	1”
Drain	“	1”
Steam inlet	“	¾”
Steam outlet	“	¾”
Compressed air	mm	Ø8

DIMENSIONS		
Depth	mm	2300
Width	mm	1905
Height	mm	2380