



HEAVY-DUTY SOFTMOUNT

WASHER EXTRACTOR

Model No.

LPW-600FD

LE PROTEK HEAVY-DUTY SOFTMOUNT WASHER EXTRACTOR

LeProtek softmount washer extractors feature heavy-duty vibration absorbing suspension system. They are designed for easy installation on various floors. The high-speed extraction up to 350G reduces linen water retention, saving significant drying time and energy. The uniquely designed 3D stereoscopic honeycomb shaped inner drum with perforated lifters, touchscreen control, and ergonomic structure create profitable and comfortable laundry environments.

Tilting option is available for 100/120kg machines to reduce labor during loading and unloading.

ADVANTAGE AND FEATURE

- Stainless steel drum and tub for anti-corrosion protection.
- Clad steel panels resist rust and fingerprints, maintaining a pristine appearance for your laundry. Optional stainless-steel panels available.
- The uniquely designed 3D stereoscopic honeycomb-shaped inner drum with perforated lifters improves cleaning results, promotes faster draining, and reduces clothing damage.
- Permanently lubricated bearings require no maintenance.
- Heavy-duty suspension system, in conjunction with an intelligent electronic balancing system, efficiently absorbs vibrations, reduces out-of-balance occurrences, and enables extraction G force up to 350 for shorter drying times.



- Large door opening for easy loading and unloading of linen.
- All casting parts are well processed and painted, ensuring machine longevity even in humid and harsh working environments.
- Mechanical and electronic double door locks, along with an emergency stop, provide maximum safety.
- Standard configuration includes 5 chemical compartments and 5 hoses for dosing pumps.
- Heavy-duty pneumatic water valves control water inlet, drain, and steam.
- Advanced inverter drive system ensures smooth start-up and energy savings, enabling longer machine life.



CONTROL

The full-color touchscreen control offers 50 programs, which are freely programmable and available in multiple languages to accommodate diverse customers worldwide. Features USB connection for program upload/download and software upgrades, along with networking capabilities for remote monitoring.

PRODUCT PARAMETER:

MODEL	LPW-600FD	
Control		Touch
Capacity 1:9-10	kg	60
Cylinder Diameter	mm	1078
Cylinder Depth	mm	620
Volume	liter	565
Door Centre to Floor	mm	1184
Cold Water Inlet	inch	1.5
Hot Water Inlet	inch	1.5
Steam inlet	inch	1
Compressed air inlet*	mm	8
Drain Diameter	mm	125
Motor Power	kW	7.5
Three-phase heating power	kW	30
Max. Extract Speed	RPM	762
G-Force	-	350
Power Supply	380V/50Hz/60Hz/3Ph	
Overall Width	mm	1619
Overall Depth	mm	1492
Overall Height	mm	1965
Net Weight	kg	1910
Packing Width	mm	1719
Packing Depth	mm	1592
Packing Height	mm	2115