



**Le Protek Soft Mount  
Washer Extractor**

**LPSWE Series**

Model No. LPSWE-25E

# LEPROTEK SOFTMOUNT WASHER EXTRACTOR



*Molded processing to ensure the precision  
New appearance has industrial aesthetics  
The belt is the V-belt to ensure the high-speed  
operation*

- 1. The inner and outer drum are all made of stainless steel. The inner adopts advanced non-marking spinning process, so the drum is hard, long-life and durable. The hi-extract speed can reach more than 800 rpm.*
- 2. The belt is the V-belt, which is more than several times of the life of ordinary belt.*
- 3. Imported bearings and shaft seal, longer service life. The gap between the inner drum and external tub is very small, so the temperature will heat up quickly and the water and electricity can be saved.*
- 4. Frequency conversion speed control can meet the high-speed requirements, low noise, good stability.*
- 5. Adopting compound suspension system, which effectively prevents the unbalanced vibration during the dehydration; the equipment is suitable for any floor, and the suspension rate reaches 97%.*

# SPECIFICATION

SPECIFICATION	UNIT	LPSWE-25E
Rated Capacity	kg	25
Drum Dimension	mm	φ780*525
Water inlet	mm	DN20
Steam inlet	mm	DN15
Water outlet	mm	DN50
Water pressure	Mpa	0.2-0.4
Steam pressure	Mpa	0.4-0.6
Motor	kw	4
Heating power	kw	15
Net weight	kg	880
Dimensions (D*D*H)	mm	970*1100*1450