



Manual Press

42/52MSR & 47UMSR Utilities
47/48MSR Leggers



- Adjustable head pressure
 - No compressed air or electricity required
 - Powder-coated metal table - resists wear and tear
 - Head released by hand-activated button on the handle
 - Head closes by hand, then locks with large foot pedal
- Options: Iron attachment, hand iron, sleeve board and water spray

www.forentausa.com

Tel: 423-586-5370 • Email: info@forentausa.com

Made in USA

"M" SERIES SPECIFICATIONS

Steam connections:

- 1/2 NPT for supply and condensate
- 75-85 psi (0.52-0.59 MPa)
- Steam consumption at 80 psi(0.55 MPa):
- 1 BHP(34.4 lb/hr)(15.6 kg/hr) MRS models
- 1.25 BHP(43.1 lb/hr)(19.5 kg/hr) MSRS models

Vacuum connection (MSR model)

- 1-1/4 NPT
- 20-30 inches of water (50-75 millibar)
- 75 cubic feet/minute (127 cubic meters/hour)

Steam Vacuum exhaust connection (MSRS models):

- 1-1/4 NPT

Electrical connection for optional 120 volt vacuum:

- 110-120 VAC single-phase, 60 Hz, 8.1 amps, (UL motor)
- Power cord connected

Electrical connection for optional 220 volt vacuum:

- 220 VAC single-phase, 60 Hz, 4.1 amps, (UL motor)
- Power cord connected

Optional hand iron electrical connection:

- 115 VAC or 230 VAC single-phase, 50/60 Hz
- Conduit connection
- 800 watts
- Approximate hourly consumption: 0.5 KWH

Optional water spray cold water connection:

- 1/4 NPT
- 40-80 psi (0.3-0.55 MPa)
- 1 gallon/minute (3.8 liter/minute)

Optional Attachment Kits

K-697 All-Steam Iron Attachment

K-198 Sleeve Board

K-699 Water Spray

K-707-1 Integrated Vacuum, 120 Volt, 1 Ph.

K-707-2 Integrated Vacuum, 220 Volt, 1 Ph.

BUCK DIMENSIONS (unpadded)

